#### $\bullet \quad \bullet \quad \bullet \quad \bullet$

# **Elektro** GENESIS

Cherish your life, Cherish your health!

# WITH PULSE-VACUUM SYSTEM

## TABLE TYPE STEAM STERILIZERS



## MODEL: TM-XD20DV Table type steam sterilizers with pulse-vacuum system

The unit disinfects and sterilizes the objects with saturated steam, by the means of pulsely exhausting the cold air to clear the efforts from which to the temperature, and make the objects completely drying by the way of vacuum-exhausting and jacket baking. By using the physical characteristics of the pressured saturated steam will releasing plenty of hot while condensing, the unit will keep the sterilizing objects wet and at high temperature in a given time, which spoils the virus and the spores together, and good sterilizing efforts will be received.

#### PARAMETER

Chamber Volume:	20 Liters
Max working temperature:	134°C
Max working pressure:	0.22 mpa
Adjusted sterilizing temperature range:	105°C ~ 134°C
Adjusted timer range:	1~99 mins
Adjusted drying time range:	1~99 mins
Vacuum limit:	-0.08 mpa
Heat Average:	≤±1°C
Power supply:	AC220V/50HZ
Dimension:	56*47*40 cm
Transport dimension:	66*56*50 cm
Gross/Net Weight	52kg/47kg

• We reserve the right for the modification of the dimension and the weight

#### **CHARACTERISCTICS:**

- The sterilizing procedure is automatically controlled, it is not necessary to be supervised, and used conveniently.
- A complete solution to Pulse vacuuming for easy Sterilization in Shortest time for wrapped or unwrapped objects, hollow equipment.
- Drying function.
- With inner printer, which record the full procedure of the sterilization.
- With Bowie & Dick testing function, which is for the steam penetrating testing.
- Self-testing malfunction, easy to maintain.

#### Safety functions:

• Safety locking: the steam can not enter the chamber and the unit will alarm when the door is not closed tightly, and the door can not the open when the inner pressure is exceed 0.027 mpa.

#### **Over pressure protection:**

If the pressure exceed the working pressure, the safety valve will exhausting the air.

#### Low water protection:

The unit can not be started if the water don't reach the high level, and the power will cut off directly.

#### **Over current protection:**

The broker will cut off the power by the over current happened.

### No. 7/24 Stebondale Street, London, United Kingdom

Authorized Distributor: Goldengate Holdings Limited Dubai, U.A.E

#### www.elektrogenesis.com

mea@elektrogenesis.com



**+971 58 912 1046 | +971 56 779 7033**